

# UV System Dulcodes MP

Effective solution for the treatment of swimming pool water – designed for the decomposition of combined chlorine.



## Flow up to 569 m<sup>3</sup>/h

The UV system Dulcodes MP is fitted with output-optimised medium-pressure lamps. They guarantee the efficient photochemical decomposition of combined chlorine in swimming pool water. The system is tolerant to the most harsh conditions in warm, humid plant rooms enriched by aggressive chemicals. The robust and conventional ballast technology remains completely unaffected by this.

Efficient cleaning of the lamp protection tubes during operation is possible with ease. The lamp protection

tubes can either be cleaned by a manual wiper or by the optionally extendible motor-driven automatic wiper.

The Dulcodes MP is a compact inline system. Thanks to its flexible flange options, the system can be used with ease for different nominal widths of circulation rate. The UV reactor is designed in such a way that no UV radiation can escape from the reactor. This means that the system can be installed directly in a plastic pipe. The free choice of the fitting position simplifies installation and retrofitting in the extreme.

## Your benefits

- Simple installation, thanks to the compact inline system, ensures minimum installation costs and fast retrofitting.
- Maximum flexibility when installing, thanks to free choice of the fitting position and direct installation in plastic pipes, as no UV radiation escapes from the reactor.
- Automatic switching on and off based on the chloramine value, for example used in conjunction with the DULCOMARIN® II.
- Unbeatably simple and quick maintenance: all maintenance work can be carried out quickly and conveniently from one side.
- Manual power control for optimum adaptation of the system to the respective capacity requirement (not for Dulcodes 1 x 0.65MP and 1MP).
- Manual or automatic wiper system for the efficient removal of deposits on the lamp protection tube. The wiper system can be easily retrofitted.

## Field of application

- Process water
- Swimming pool water

# UV System Dulcodes MP

Effective solution for the treatment of swimming pool water – designed for the decomposition of combined chlorine.

## Technical Data

Type	Max. flow m <sup>3</sup> /h	Lamp power W	Connected load kW	Reactor length mm	Minimum clearance for service mm	Empty weight/ Operating weight kg	DIN connector
<b>1x0,65MP</b>	20.0*	650	0.75	500	335	21/31	DN 65/80
<b>1x1MP</b>	58.0*	1.000	1.10	700	400	31/47	DN 100/125
<b>1x2MP</b>	102.0*	2.000	2.10	700	500	38/65	DN 125/150
<b>1x3MP</b>	205.0*	3.000	3.20	800	600	52/118	DN 200/250
<b>2x2MP</b>	278.0*	4.000	4.20	900	1,000	78/166	DN 200/250
<b>2x3MP</b>	379.0*	6.000	6.20	900	1,000	78/166	DN 200/250
<b>3x3MP</b>	569.0*	9.000	9.20	900	1,000	78/166	DN 250/300

\* 98 %/cm transmission; 600 J/m<sup>2</sup> UV dose for the breaking down of combined chlorine

<b>Lamp type</b>	Powerline MP medium-pressure lamp
<b>Controller type</b>	Comfort controller
<b>Permissible operating pressure</b>	6 bar
<b>Permissible ambient temperature</b>	5 – 40 °C
<b>Permissible water temperature</b>	5 – 40 °C