2 Tank Saturator - Vacuum Load System





Chemical Loading

- Chemical Loading via a Prominent Vacuum Loader system.
- Low dust.
- Integrated dust reducing vent tank.
- Exhaust filtered and piped outside of the room.
- Increased operator safety.

Tanks

- Twin tanks integrated into a single package. Custom fabricated tank / baffles.
- Two blank sides on the tanks, allowing placement in the corner of the room.
- Available as a Vacuum Loader or with a Prominent Bottle loader fitted.
- One tank makes a batch, the chemical is aggressively mixed and then allowed to settle.
- The batch is transferred regularly to top up the second tank.
- Second tank contains clean saturated fluoride solution. Ready to be dosed at any time.
- Only a small amount of fluoride is required to be loaded into the system. This will still maintain complete saturation of the solution in the second tank. Unlike a conventional saturator which requires large volumes of chemical to operate.
- When tank cleaning is required, only a small amount of waste chemical needs to be removed.

SYDNEY OFFICE

Unit 4, 4 Narabang Way, BELROSE NSW 2085 P 02 9450 0995 F 02 9450 0996 sales@prominentfluid.com.au

QUEENSLAND OFFICE Unit 1, 68 Murdoch Circuit, ACACIA RIDGE QLD 4110 P 07 3213 1900 F 07 3272 0445 pfcqld@prominentfluid.com.au





Water Softener

- A water softener and water heater are supplied with the system.
- Softener removes the "hardness" from the service water. The fluoride in the tank lasts longer with the "hardness" removed.
- Automatic regeneration of the water softener does not require intervention by the operator.
- The water heater heats up the water entering the tank, this results in less time for chemical to saturate.
- These components are fully integrated into the system.

Equipment: General

- Compact system made in modules.
- Easy to place in the room, especially with restricted space.
- Layout variation possible with modular design, allows for difficult rooms.
- Easy to wire junction box in each module. Connect with multicore cabling.
- One system can operate over a large flow range. This allows the system to be upgraded to larger flow rates in the future.
- Lower waste generated and easier cleaning.
- Latest modern design made to be very efficient.

www.prominentfluid.com.au

VICTORIA OFFICE

Unit 1/21-22 National Drive HALLAM VIC 3803 P 03 8795 7430 F 03 8975 7431 pfcvic@prominentfluid.com.au WESTERN AUSTRALIA OFFICE Office 11, 34 Welshpool Road Welshpool WA 6106
E: pfcwa@prominentfluid.com.au

ProMinent[®]