

# Chlorine Dioxide System Bello Zon<sup>®</sup> CDLb with Multiple Points of Injection

The modular customised solution for several ClO<sub>2</sub> points of injection with only one generation system.



**0 – 120 g/h capacity with storage of up to 60 g of chlorine dioxide for peak metering. Max. flow rate at 0.2 ppm ClO<sub>2</sub> metering capacity of 600 m<sup>3</sup>/h, up to 6 points of injection possible as standard**

The Bello Zon<sup>®</sup> chlorine dioxide systems for multiple metering are divided into three different concepts designed to respond to specific customer requirements. These concepts are used where several points of injection need to be supplied with ClO<sub>2</sub> from a single ClO<sub>2</sub> system. Up to 6 points of injection can be selected as standard depending on the chosen concept.

This concept consists of two main components, the CDLb system and a metering panel, on which all the metering

components are mechanically and, optionally, electrically ready mounted.

This concept consists of a stainless steel frame, on which the BelloZon<sup>®</sup> CDLb system and the metering components are mechanically and electrically mounted in full. There is a stainless steel control cabinet with a main switch that contains the central power supply and control system for all electrical components.

## Your benefits

- Very easy way to provide several points of injection according to requirements
- Cost-effective way to provide several points of injection
- Outstanding operating safety and reliability, thanks to intrinsically safe process control
- Ultra-simple process integration
- Location-independent system monitoring in real time via the DULCOnneX platform: Improved process reliability. Reliability and transparency due to real-time monitoring, individual alarms and automated reports.

## Field of application

- All applications which require more than one point of injection
- Disinfection in the food and beverage industry. Especially with bottle rinsers, CIP (cleaning in place), bottle washing machine and in fruit / vegetable washing
- Legionella control and prevention, e.g. in hotels or hospitals (cold and hot water metering)
- Market gardening: germ-free irrigation and sprinkler irrigation water
- Treatment of cooling water and potable water
- Filter disinfection, e.g. in swimming pools

# Chlorine Dioxide System Bello Zon<sup>®</sup> CDLb with Multiple Points of Injection

The modular customised solution for several ClO<sub>2</sub> points of injection with only one generation system.

## Technical Data

- External storage module
- Internal storage tank (only with the "Modular, loose components" and "Modular, metering components pre-assembled on a panel" concepts)
- Terminal box with optional main switch (only with the "Modular, metering components pre-assembled on a panel" concept)
- Stainless steel cabinet with main switch and emergency relay (only with the "Plug and Play on stainless steel frame" concept)