

# Peristaltic Pump DULCO<sup>®</sup>flex DF2a

The optimum pump product range for use in swimming pools, hot tubs, and spa zones.



## Capacity range 0.4 – 2.4 l/h at max. 1.5 bar back pressure

The feed chemical is transported by the rotor squeezing the hose in the direction of flow. This explains why there is no need for valves. The feed chemical is thus handled with

care. Typical applications: wherever lower pump pressure is sufficient. For example when metering conditioners in private pools.

## Your benefits

- Smooth inner wall reduces deposits.
- Hose materials: PharMed<sup>®</sup> or Viton<sup>®</sup>
- Virtually silent operation
- Simple handling
- Enhanced service life of the hose due to spring-loaded rollers, which keep the rolling pressure constant
- Robust and protected against spray water from all sides: Housing made of impact-resistant and chemical-resistant PPE

## Field of application

- Meters conditioners in private pools
- Meters belt lubricants in bottling machines
- Meters cleaning agents in dishwashers

# Peristaltic Pump DULCO<sup>®</sup>flex DF2a

The optimum pump product range for use in swimming pools, hot tubs, and spa zones.

## Technical Data

Type	Capacity		Frequency	Connector size	Suction lift	Intake head
	bar	l/h	rpm	o Ø x i Ø	m WC	m WC
0204	1.5	0.4	5	6x4/10x4	4	3
0208	1.5	0.8	10	6x4/10x4	4	3
0216	1.5	1.6	20	6x4/10x4	4	3
0224	1.5	2.4	30	6x4/10x4	4	3

Admissible ambient temperature: 10-45 °C

Power consumption approx.: 5 W

Switching duration: 100%

Enclosure rating: IP 65

All data refers to water at 20 °C.