

Peristaltic Pump DULCO[®]flex DFBa

Low and medium pump capacities



Feed rates of up to 649 l/h at 8 bar

The peristaltic pump DULCO[®]flex DFBa is equipped with rollers and fabric-reinforced hoses for tough industrial use.

Pumps with a Halar-coated pump housing can be produced for use in the chemical industry.

Your benefits

- Simple to operate
- Reversible pumping direction
- Hose materials suitable for various chemicals
- Simple and quick hose change
- Ideal for pumping pasty, high-viscosity, abrasive and gaseous media
- Self-priming

Field of application

- Chemical industry
- Waste water
- Mining

Peristaltic Pump DULCO[®]flex DFBa

Low and medium pump capacities

Technical Data

Hose	NR, NBR, EPDM, NR-A, Norprene, NBR-A, Hypalon, Tygon
Self-priming	up to 8 m
Rollers / shoes	Rollers

Type	Feed rate / revolution	Delivery rate at max. back pressure		Hose diameter (internal)	Max. solids	Weight without drive	Connection DN
	l/rev.	bar	l/h	mm	mm	kg	
DFBa 010	0.02	8	60	10	2.5	6	3/8"
DFBa 013	0.04	8	100	13	3.3	6	3/8"
DFBa 016	0.09	8	188	16	4.0	13	3/4"
DFBa 019	0.12	2	671	19	4.8	13	1"
DFBa 022	0.24	8	649	22	5.5	22	1"