

DULCOTEST® Temperature Sensors

Temperature measurement with the reliable DULCOTEST® sensors



Measuring ranges 0 – 100 °C

Temperature measurement can take place separately or as a correction variable for other measured parameters.

Temperature measurement is used universally, either to directly measure the temperature or for temperature compensation when measuring the following parameters:

- pH
- Fluoride
- Conductivity
- Chlorine dioxide
- Hydrogen peroxide

Your benefits

- Select Pt 100 or Pt 1000, depending on measuring range and accuracy required.
- Sturdy design with dimensions of a standard pH sensor; the sensor element is integrated in a chemically inert glass sleeve.
- Easily installed in a similar way to standard pH sensors with a PG 13.5 thread in existing fittings.
- Transmitter with display/operation and without display/operation for transmission/conversion of the primary signal into a 4-20 mA signal and for transmission to a central control unit (PLC).

Field of application

Temperature measurement is used universally, either to directly measure the temperature or for temperature compensation.

DULCOTEST® Temperature Sensors

Temperature measurement with the reliable DULCOTEST® sensors

Technical Data

DULCOTEST® Temperature Sensors

Temperature measurement with DULCOTEST® sensors: Can be used for direct temperature measurement or temperature compensation during measurement of pH, fluoride, conductivity, chlorine dioxide or hydrogen peroxide.

Your benefits

- Select Pt 100 or Pt 1000, depending on measuring range and accuracy required.
- Sturdy design with dimensions of a standard pH sensor; the sensor element is integrated in a chemically inert glass sleeve.
- Easily installed in a similar way to standard pH sensors with a PG 13.5 thread in existing fittings.
- Transmitter with display/operation and without display/operation for transmission/conversion of the primary signal into a 4-20 mA signal and for transmission to a central control unit (PLC).

Temperature	0 ... 100 °C
Max. pressure	10.0 bar
Thread	PG 13.5
Electrical connection	SN6
Typical applications	Temperature measurement and pH temperature correction.

	Order no.
Pt 100 SE temperature sensor	305063
Pt 1000 SE	1002856