

HOW TO ORDER



ACCUDRAW[®] Calibration Cylinders

Sizing and Ordering Information:

ACCUDRAW Standard Materials of Construction

AC = All polypropylene construction (see below for options)
 PV = All polyvinylchloride construction (see below for options)
 ACS = Glass*

Example: AC#1-1000-B

AC = PP (polypropylene)
 1 = Bottom threaded connection only
 1000 = 1000 ml
 B = BSP Thread

Note: Cylinders are NOT pressure vessels

e.g. Part # **AC #1 1000 B**

Type:
 AC = Polypropylene
 PV = PVC
 ACS = Glass *

Style:
 1 = Bottom threaded conn. only
 2 = Top/Bottom threaded conn
 3 = Bottom threaded conn. c/w removable vented dust cap
 4 = Top/Bottom threaded conn. c/w removeable "O" ring sealed top and float ring level indicator
 *Glass calibration cylinders available in Style 2 only

Graduation Scale:
 PP Grad in ml only
 PVC Grad in ml/GPH
 Glass Grad in ml only

Std. connection is NPT threaded
Optional: add suffix as follows
 S = Socket weld connection (PVC only)
 GTV = Glass/TFE construction
 GKV = Glass/PVDF construction
 GCV = Glass/CPVC construction
 GSV = Glass/SS construction
 B = BSPT Thread
 F = Flanged (Substitute E for V for EPDM wetted "O" Ring seal)

Size:	Material
100 = 100 ml (1.6 GPH)	PP, PVC, Glass
250 = 250 ml (4 GPH)	PP, PVC, Glass
500 = 500 ml (8 GPH)	PP, PVC, Glass
1000 = 1000 ml (16 GPH)	PP, PVC, Glass
2000 = 2000 ml (32 GPH)	PP, PVC, Glass
4000 = 4000 ml (64 GPH)	PP, PVC, Glass
6000 = 6000 ml	Glass Only
8000 = 8000 ml	Glass Only
10000 = 10000 ml (160 GPH)	PVC, Glass
20000 = 20000 ml (320 GPH)	PVC, Glass

Custom Sizes and materials Available

As Manufactured By:



PRIMARY FLUID SYSTEMS INC. Tel: (905) 333-8743
 Fax: (905) 333-8746
 North America Toll Free – 1-800-776-6580
 E-Mail: primary@primaryfluid.com
<http://www.primaryfluid.com>